

KONTAKT 300/K PROFI TWIN POWER

DO YOU REALLY NEED A LOT OF POWER HIDDEN IN A COMPACT PORTABLE COOLER?



CZECH UP YOUR BEER
COOLING AND DISPENSING SYSTEMS

COMPACT & POWERFUL

Thanks to their unique design with two cooling compressors, KONTAKT 300 TWIN POWER Green Line is the most powerful cooler in its class.





KONTAKT 300/K PROFI TWIN POWER GREEN LINE

Do you really need a lot of power hidden in a compact portable cooler?

Then reach for the KONTAKT 300/K PROFI NEW GREEN LINE dispensing machine and you can't make a mistake. KONTAKT 300/K PROFI TWIN POWER Green Line model is professional beverage cooler which can be used more than just a mobile bar. Thanks to their unique design with two cooling compressors, KONTAKT 300 TWIN POWER Green Line is the most powerful cooler in its class. It is designed for professional cooling, dispensing and serving perfectly chilled beer and other beverages. Serving up to 600 perfectly chilled beers per hour will not disappoint you even in larger restaurants, bars, festivals or outdoor pop-up mobile bars.



<< KONTAKT 300/K PROFI TWIN POWER GREEN LINE ILLUMINATED ADVERTISING - Full scale advertising space facing in the direction of the customer with customised logos.

< KONTAKT 300/K PROFI TWIN POWER GREEN LINE QUICK INSTALLATION - The taps are customized and easy to install. You can choose any of traditional or ball tap. The design of KONTAKT 300 TWIN POWER allows the cooler to be used as a pre-cooler, an undercounter cooler and allows possibility of combination with dispense tower.

| BENEFITS AND USEFUL FEATURES

HIGH OUTPUT - the design of the two-compressor cooling unit with use of eco-friendly refrigerant R-290 allows a maximum cooling output of up to 300 l/ hour without the need to use an additional pre-cooler.

LOW INPUT POWER - the machine's high output is achieved with a maximum input power of under 6A.

SIMPLE CONNECTION - 2x35 m long two-circuit stainless steel tubing with 10 mm diameter embedded in a thermoblock. The tubing is fitted with a stainless steel screwing on both the inlet and outlet to connect the beverage supply (INLET - external 5/8"/ OUTLET - internal 5/8").

AIR COMPRESSORS - The two quiet inbuilt air compressors feature a separate receiver to prevent pressure fluctuations during dispensing. Regulation of pressure is 1- 4 bars.

QUICK INSTALLATION - The taps are customized and easy to install.

UNIVERSAL USE - the design of KONTAKT 300 TWIN POWER allows the cooler to be used as a pre-cooler, an undercounter cooler and, above all, as a portable, powerful cooler.

ILLUMINATED ADVERTISING - full scale advertising space facing in the direction of the customer with customised logos.

EASILY PORTABLE - the robust construction of the machines's two sliding stainless steel handles enables ease of portability.

HYGIENE AND DURABILITY - the entire body and coils are made of stainless steel. The materials used meet the strictest hygienic standards and guarantee long service life of the cooler.

RECYCLABLE MATERIALS - the cooler is made of fully recyclable materials.

VERSATILITY - Can also be used with a bar dispense tower.

GREEN LINE - LINDR GREEN LINE technology is environmentally friendly thanks to the use of eco-friendly refrigerant R-290. Thanks to this design, each product achieves 20 % higher energy efficiency and 20 % lower energy consumption. We have introduced an energy saving system in the production.

LINDR THERMAL BLOCK - the compressor cooling unit uses the power input for direct transfer to chilling, which guarantees minimum energy usage. Perfectly chilled beer is ready within a few minutes after switching the cooler on.

STAINLESS CONSTRUCTION - the entire body and the coil of the cooler are made of stainless steel. The materials used meet the strictest hygienic standards and guarantee long service life of the cooler.

PERFORMANCE, QUALITY, SIZE - the best performance/ quality/ size ratio.



WE KNOW THAT DETAILS MATTER



SIMPLE CONNECTION

2x35 m long two-circuit stainless steel tubing with 10 mm diameter embedded in a thermoblock. The tubing is fitted with a stainless steel screwing on both the inlet and outlet to connect the beverage supply.

(INLET - external 5/8"/ OUTLET - internal 5/8")



KONTAKT 300/K PROFI TWIN POWER GREEN LINE



PRODUCT MODEL	KONTAKT 300/K PROFI TWIN POWER GL
COOLING POWER OF THE COMPRESSOR (HP)	2X 1/2
COOLING POWER OF THE COMPRESSOR (W)	2X 1488
MAXIMUM COOLING CAPACITY TO 0 °C / TK 45 °C (L/HOUR)	300
CONTINUOUS COOLING PERFORMANCE (L/HOUR)	240
THERMAL GRADIENT ΔT (°C)	10
AIR COMPRESSOR (BAR)	YES
AIR COMPRESSOR PRESSURE (BAR)	REGULATION 1,0-4,0
NUMBER OF TAPS (PCS)	2
NUMBER OF COOLED BEVERAGES (PCS)	2
LENGTH OF COOLING COILS (M)	2X35,0
DIAMETER OF COOLING COIL (MM)	10X0,5
POWER (W)	1380
AMPERAGE (A)	6,00
NET WEIGHT (KG)	76,0
REFRIGERANT TYPE	R290
VOLTAGE (V)	220-240V 50HZ-1
BEVERAGE CONNECTION (FITTINGS)	65/8"
AIR CONNECTION (FITTINGS)	65/8"
CUSTOMIZED OPTIONS	
CHOICE OF TAP	YES
BEVERAGE CONNECTION - STAINLESS STEEL SCREWING	NO
AIR CONNECTION - STAINLESS STEEL SCREWING	NO
POWER CABLE PLUG	YES