



CZECH UP YOUR BEER
COOLING AND DISPENSING SYSTEMS

MODEL AS-80 GREEN LINE

COOLING OUTPUT OF 45-80 L/HOUR

ADVANTAGES AND FUNCTIONAL CHARACTERISTICS OF THE AS LINDR LINE:

AS – technology of water cooling with an ice bank. This machine can provide maximum cooling output.

GREEN LINE – LINDR GREEN LINE technology is environmentally friendly thanks to the use of eco-friendly refrigerant R-290. We have introduced an energy saving system in the production. Thanks to this design, each product achieves **20% higher energy efficiency and 20% lower energy consumption.**

LINDR COOLING TECHNOLOGY – always more powerful than its electric input power.

CONSTRUCTION AND SERVICING – the modern arrangement of LINDR cooling technology ensures ease of access for potential servicing and maintenance.

PERFORMANCE, QUALITY, SIZE – the best performance/ quality/ size ratio.

These undercounter coolers are designed for professional dispensing of beverages in restaurants and bars with lower volume of beverages served. The cooling device is fitted with a pump with 6 m displacement, which allows the cooler to be placed in a cellar and still cool the beverage all the way to the tap.



✓ **GREEN LINE** – all models from the AS series are fully in GREEN LINE design.

✓ **COMFORTABLY PORTABLE** – easy and safe handling thanks to two stainless steel handles on the sides of the device.

✓ **EQUIPMENT** – thermostat, cooling coil, speedfit fittings, stirrer with a pump to ensure even temperature across the entire water bath and proper cooling of the beverage all the way to the tap.

TECHNICAL PARAMETERS



AVAILABLE CUSTOM MODIFICATION OPTIONS

POWER CABLE PLUG

Note
Selected models are also available in 115 V/60 Hz or 220 V/60 Hz voltage.
Other custom modifications are also available (contact us).

YES



PRODUCT MODEL	AS-80 GL 2x cooling coils	AS-80 GL 4x cooling coils
COOLING POWER OF THE COMPRESSOR (HP)	1/4	1/4
COOLING POWER OF THE COMPRESSOR (W)	630	630
MAXIMUM COOLING CAPACITY TO 0°C / TK 45°C (L/HOUR)	80	80
CONTINUOUS COOLING PERFORMANCE (L/HOUR)	45	45
THERMAL GRADIENT ΔT (°C)	10	10
ICE BANK (KG)	5-10	5-10
DISPLACEMENT OF RECIRCULATION PUMP (M)	6	6
NUMBER OF COOLED BEVERAGES (PCS)	2	4
NUMBER/ LENGTH OF COOLING COILS (M)	2/ 11	2/ 11, 2/ 8
POWER (W)	506	506
AMPERAGE (A)	2,20	2,20
NET WEIGHT (KG)	26,0	27,0
TYPE OF REFRIGERANT	R290	R290
VOLTAGE	220-240V 50HZ-1	220-240V 50HZ-1
CONNECTION BEER/ AIR - SPEEDFIT FITTINGS	3/8, 1/2	3/8, 1/2

