



MODEL PYGMY 25/K GREEN LINE

CZECH UP YOUR BEER
COOLING AND DISPENSING SYSTEMS

PYGMY series dispensing systems are designed for professional cooling, dispensing and serving of perfectly chilled beer and other beverages at home, on small garden parties, company celebrations etc. They are the pinnacle among small table-top coolers.

MODELS PYGMY 20, 20/K, 25, 25/K

GREEN LINE

The PYGMY 25 (25/K) cooler is fitted with an aftercooled tap that ensures proper cooling even for small amounts of first beer. Small size and handle on the top allow easy handling and transport.



BENEFIT AND FUNCTIONAL CHARACTERISTICS
OF LINDR CONTACT DISPENSING SYSTEMS:

GREEN LINE – LINDR GREEN LINE technology is environmentally friendly thanks to the use of eco-friendly refrigerant R-290. We have introduced an energy saving system in the production. Thanks to this design, each product achieves **20% higher energy efficiency and 20% lower energy consumption.**

LINDR THERMAL BLOCK – the compressor cooling unit uses the power input for direct transfer to chilling, which guarantees minimum energy usage. Perfectly chilled beer is ready within a few minutes after switching the cooler on.

LINDR COOLING TECHNOLOGY – always more powerful than its electric input power.

STAINLESS CONSTRUCTION – The entire body and the coil of the cooler are made of stainless steel. The materials used meet the strictest hygienic standards and guarantee long service life of the cooler.

PERFORMANCE, QUALITY, SIZE – the best performance/ quality/ size ratio.

VERSATILITY – Can also be used with a bar dispense tower.

✓ **GREEN LINE** – all models from the PYGMY series come in full GREEN LINE design (except for PYGMY 30/K PROFÍ).

✓ **IMPROVED PERFORMANCE** – PYGMY series dispensing systems boast an increased output of 20-35 l/h, allowing you to serve 40-70 perfectly chilled drinks an hour.

✓ **KEG PRESSURISATION** – MODELS PYGMY 20/K, 25/K GREEN LINE are equipped with a unique system of a built-in, silent, high-quality air compressor fitted with a noise dampener and a molecule filter for incoming air.

✓ **PERFECT DRAUGHT BEER** – model PYGMY 30/K PROFÍ is fitted with a regulator with pressure gauge to set the optimal pressure for dispensing different types of beverages.

✓ **COMFORTABLY PORTABLE** – easy and safe handling of the system thanks to the small size and a handle on top.

✓ **EQUIPMENT** – thermostat allowing smooth and precise regulation of beverage temperature, dispensing tap, tap wrench, drip tray and speedfit fittings for easy connection.

TECHNICAL PARAMETERS



AVAILABLE CUSTOM MODIFICATION OPTIONS

CHOICE OF TAPS

YES



BEER/ AIR STAINLESS STEEL SCREWING - 6 5/8"



POWER CABLE PLUG



Note

Selected models are also available in 115 V/60 Hz or 220 V/60 Hz voltage.

Other custom modifications are also available (contact us).

PRODUCT MODEL	PYGMY 25/K GI
COOLING POWER OF THE COMPRESSOR (HP)	1/8
COOLING POWER OF THE COMPRESSOR (W)	310
MAXIMUM COOLING CAPACITY TO 0°C / TK 45°C (L/HOUR)	35
CONTINUOUS COOLING PERFORMANCE (L/HOUR)	25
THERMAL GRADIENT ΔT (°C)	10
AIR COMPRESSOR (BAR)	YES, AUTOMATIC 2,8-3,2
NUMBER OF TAPS (PCS)	1
NUMBER/ LENGHT OF COOLING COILS (M)	1/ 11,5
POWER (W)	368
AMPERAGE (A)	1,60
NET WEIGHT (KG)	16,5
TYPE OF REFRIGERANT	R290
VOLTAGE	220-240V 50HZ~1
CONNECTION BEER/ AIR - SPEEDFIT FITTINGS	3/8, 5/16

