



CZECH UP YOUR BEER
COOLING AND DISPENSING SYSTEMS

MODEL AS-110 INOX TROPICAL GREEN LINE

COOLING OUTPUT OF 60-110 L/HOUR

ADVANTAGES AND FUNCTIONAL
CHARACTERISTICS OF THE AS LINDR LINE:

These undercounter coolers are designed for professional dispensing of beverages in restaurants and bars. Models from the AS-110 series are fitted with a pump with 6 m displacement, which allows the cooler to be placed in a cellar and still cool the beverage all the way to the tap.

| TROPICAL CONDITIONS

AS INOX TROPICAL features a thickened 45 mm insulation, even on the cover housing, and is designed for extreme tropical conditions. This device can fully function even at ambient temperatures of up to 45°C.



AS – technology of water cooling with an ice bank. This machine can provide maximum cooling output.

GREEN LINE – LINDR GREEN LINE technology is environmentally friendly thanks to the use of eco-friendly refrigerant R-290. We have introduced an energy saving system in the production. Thanks to this design, each product achieves **20% higher energy efficiency and 20% lower energy consumption.**

LINDR COOLING TECHNOLOGY – always more powerful than its electric input power.

CONSTRUCTION AND SERVICING – the modern arrangement of LINDR cooling technology ensures ease of access for potential servicing and maintenance.

PERFORMANCE, QUALITY, SIZE – the best performance/ quality/ size ratio.

✓ **COMFORTABLY PORTABLE** – easy and safe handling thanks to two stainless steel handles on the sides of the device.

✓ **TROPICAL CONDITIONS** – AS INOX TROPICAL features a thickened 45 mm insulation, even on the top cover, and is designed for extreme tropical conditions. This device can fully function even at ambient temperatures of up to 45°C.

✓ **GREEN LINE** – all models from the AS series are fully in GREEN LINE design.

✓ **EQUIPMENT** – thermostat, cooling coil, speedfit fittings, stirrer with a pump to ensure even temperature across the entire water bath and proper cooling of the beverage all the way to the tap.

TECHNICAL PARAMETERS



AVAILABLE CUSTOM MODIFICATION OPTIONS

POWER CABLE PLUG

Note

Selected models are also available in 115 V/60 Hz or 220 V/60 Hz voltage.
Other custom modifications are also available (contact us).

YES



PRODUCT MODEL	RS-110 INOX GL 2x cooling coils	AS-110 INOX GL 4x cooling coils	AS-110 INOX GL 6x cooling coils
COOLING POWER OF THE COMPRESSOR (HP)	1/3	1/3	1/3
COOLING POWER OF THE COMPRESSOR (W)	860	860	860
MAXIMUM COOLING CAPACITY TO 0°C / TK 45°C (L/HOUR)	110	110	110
CONTINUOUS COOLING PERFORMANCE (L/HOUR)	60	60	60
THERMAL GRADIENT ΔT (°C)	10	10	10
ICE BANK (KG)	10-20	10-20	10-20
DISPLACEMENT OF RECIRCULATION PUMP (M)	6	6	6
NUMBER OF COOLED BEVERAGES (PCS)	2	4	6
NUMBER/ LENGTH OF COOLING COILS (M)	2/ 14	2/ 14, 2/ 11	2/ 14, 2/ 11, 2/ 8
POWER (W)	621	621	621
AMPERAGE (A)	2,70	2,70	2,70
NET WEIGHT (KG)	32,0	34,0	35,5
TYPE OF REFRIGERANT	R290	R290	R290
VOLTAGE	220-240V 50HZ~1	220-240V 50HZ~1	220-240V 50HZ~1
CONNECTION BEER/ AIR - SPEEDFIT FITTINGS	3/8, 1/2	3/8, 1/2	3/8, 1/2

