



**CZECH UP YOUR BEER**  
COOLING AND DISPENSING SYSTEMS

# MODEL AS-160 INOX TROPICAL GREEN LINE

COOLING OUTPUT OF 110-160 L/HOUR

ADVANTAGES AND FUNCTIONAL  
CHARACTERISTICS OF THE AS LINDR LINE:

*These undercounter coolers are designed for professional dispensing of beverages in restaurants and bars. Models from the AS-160 series are fitted with a pump with 8 m displacement, which allows the cooler to be placed in a cellar and still cool the beverage all the way to the tap.*

## | TROPICAL CONDITIONS

*AS INOX TROPICAL features a thickened 45 mm insulation, even on the cover housing, and is designed for extreme tropical conditions. This device can fully function even at ambient temperatures of up to 45°C.*



**AS** – technology of water cooling with an ice bank. This machine can provide maximum cooling output.

**GREEN LINE** – LINDR GREEN LINE technology is environmentally friendly thanks to the use of eco-friendly refrigerant R-290. We have introduced an energy saving system in the production. Thanks to this design, each product achieves **20% higher energy efficiency and 20% lower energy consumption.**

**LINDR COOLING TECHNOLOGY** – always more powerful than its electric input power.

**CONSTRUCTION AND SERVICING** – the modern arrangement of LINDR cooling technology ensures ease of access for potential servicing and maintenance.

**PERFORMANCE, QUALITY, SIZE** – the best performance/ quality/ size ratio.

✓ **COMFORTABLY PORTABLE** – easy and safe handling thanks to two stainless steel handles on the sides of the device.

✓ **TROPICAL CONDITIONS** – AS INOX TROPICAL features a thickened 45 mm insulation, even on the top cover, and is designed for extreme tropical conditions. This device can fully function even at ambient temperatures of up to 45°C.

✓ **GREEN LINE** – all models from the AS series are fully in GREEN LINE design.

✓ **EQUIPMENT** – thermostat, cooling coil, speedfit fittings, stirrer with a pump to ensure even temperature across the entire water bath and proper cooling of the beverage all the way to the tap.

# TECHNICAL PARAMETERS



## AVAILABLE CUSTOM MODIFICATION OPTIONS

### POWER CABLE PLUG

#### Note

Selected models are also available in 115 V/60 Hz or 220 V/60 Hz voltage.  
Other custom modifications are also available (contact us).

YES



PRODUCT MODEL	AS-160 INOX GL 4x cooling coils	AS-160 INOX GL 6x cooling coils	AS-160 INOX GL 8x cooling coils
COOLING POWER OF THE COMPRESSOR (HP)	3/4	3/4	3/4
COOLING POWER OF THE COMPRESSOR (W)	1550	1550	1550
MAXIMUM COOLING CAPACITY TO 0°C / TK 45°C (L/HOUR)	160	160	160
CONTINUOUS COOLING PERFORMANCE (L/HOUR)	110	110	110
THERMAL GRADIENT ΔT (°C)	10	10	10
ICE BANK (KG)	10-30	10-30	10-30
DISPLACEMENT OF RECIRCULATION PUMP (M)	8	8	8
NUMBER OF COOLED BEVERAGES (PCS)	4	6	8
NUMBER/ LENGTH OF COOLING COILS (M)	2/ 19, 2/ 14	2/ 19, 2/ 14, 2/ 10	2/ 14, 2/ 10, 4/ 9,5
POWER (W)	874	874	874
AMPERAGE (A)	3,80	3,80	3,80
NET WEIGHT (KG)	44,5	47,0	47,0
TYPE OF REFRIGERANT	R290	R290	R290
VOLTAGE	220-240V 50HZ~1	220-240V 50HZ~1	220-240V 50HZ~1
CONNECTION BEER/ AIR - SPEEDFIT FITTINGS	3/8, 1/2	3/8, 1/2	3/8, 1/2

