



CZECH UP YOUR BEER
COOLING AND DISPENSING SYSTEMS

MODEL CWP 300 V GREEN LINE

DEVICE FOR CONTROLLED FERMENTATION

CWP 300 V GREEN LINE is a professional device whose unique structural design is intended for use primarily in winemaking. Aside from cooling, the unit is also fitted with a water heater. The device enables manual switching between cooling and heating. Winemakers use this machine to chill or ferment wine. It can be also used to ferment must. CWP 300 V GREEN LINE is fitted with a drain valve for easy draining of water from the device and with a water gauge for checking the water level.



ADVANTAGES AND FUNCTIONAL CHARACTERISTICS OF THE CWP LINDR LINE:

GREEN LINE – LINDR GREEN LINE

*technology is environmentally friendly thanks to the use of eco-friendly refrigerant R-290. We have introduced an energy saving system in the production. Thanks to this design, each product achieves **20% higher energy efficiency and 20% lower energy consumption.***

LINDR COOLING TECHNOLOGY – always more powerful than its electric input power.

CONSTRUCTION AND SERVICING – the modern arrangement of LINDR cooling technology ensures ease of access for potential servicing and maintenance.

PERFORMANCE, QUALITY, SIZE – the best performance/ quality/ size ratio.

✓ **GREEN LINE** – all models from the CWP series are fully in GREEN LINE design.

✓ **WINE FERMENTATION AND CHILLING** – possibility of use also for controlled fermentation of wine (technology chills the juice to the required temperature) or for freezing wines (precipitation and sedimentation of proteins and tartar).

✓ **COOLING/HEATING** – cooling power of CWP 300 V at TK 45°C / TO -5°C of max. 1,900 (W) / heating power of 1,800 (W).

✓ **HANDLING** – the units are fitted with 4 wheels for easier handling.

✓ **TEMPERATURE REGULATION** – smooth regulation via 2 digital thermostats with temperature range of - 6 to + 40°C.

✓ **PROBE** – CWP 300 V is fitted with an external sensor for turning the pump on and off, thus adjusting temperature in the wine tank.

TECHNICAL PARAMETERS



AVAILABLE CUSTOM MODIFICATION OPTIONS

POWER CABLE PLUG

Note
Selected models are also available in 115 V/60 Hz or 220 V/60 Hz voltage.
Other custom modifications are also available (contact us).

YES



PRODUCT MODEL

CWP 300 V GL

COOLING POWER OF THE COMPRESSOR (HP)	3/4
COOLING POWER OF THE COMPRESSOR (W)	2000
HEATING (W)	1800
CONTINUOUS COOLING PERFORMANCE (L/HOUR)	180
THERMAL GRADIENT ΔT ($^{\circ}C$)	10
DISPLACEMENT OF RECIRCULATION PUMP (M)	12
POWER (W)	2162
AMPERAGE (A)	9,40
NET WEIGHT (KG)	41,5
TYPE OF REFRIGERANT	R290
VOLTAGE	220-240V 50HZ-1
CONNECTION OF RECIRCULATION PUMP - SPEEDFIT FITTINGS	1/2

